

STAHLSCHEREN










HSS SERIE

15 MODELLE STAHLSCHEREN VON 300 BIS ZU 21.850 KG FÜR BAGGER VON 4 BIS 280 TONNEN



			HSS-3RV	HSS-6RV	HSS-10RV	HSS-14RV	HSS-22RV	HSS-28RV	HSS-34RV
(1)	Baggerklasse	T.	4 - 5	5 - 8	8 - 12	12 - 18	18 - 23	23 - 30	30 - 38
	Gewicht	Kg.	300	610	1020	1360	2180	2840	3360
	Maulweite	mm.	265	340	405	475	535	575	615
	Maultiefe	mm.	230	320	355	385	445	495	545
	Arbeitsdruck	Bar	220	300	380	380	380	380	380
	Ölvolumenstrom öffnen/schließen	L/min.	80 - 100	80 - 150	100 - 150	150 - 250	180 - 250	200 - 300	200 - 300
	Arbeitsdruck beim rotieren	Bar	120	120	120	180	180	180	180
	Ölvolumenstrom beim rotieren	L/min.	5	10	10	10	10	10	10
	Öffnen/schließen	Sec.	1.0 / 2.8	1.0 / 2.0	1.9 / 3.6	1.9 / 2.5	2.0 / 2.8	2.9 / 2.9	3.9 / 4.1

(1) Empfohlene Bagger / Anbauteil Kombination

		HSS-45RV	HSS-52RV	HSS-62RV	HSS-82RV	HSS-110RV	HSS-140RV	HSS-180RV	HSS-220RV
 (1) Baggerklasse	T.	40 - 50	52 - 65	55 - 70	75 - 100	120 - 150	140 - 170	140 - 210	200 - 280
 Gewicht	Kg.	4380	5160	6480	8230	11680	14300	18340	21850
 Maulweite	mm.	680	730	780	845	920	1078	1100	1180
 Maultiefe	mm.	600	640	690	710	780	1020	1080	1130
 Arbeitsdruck	Bar	380	380	380	380	380	380	380	380
 Ölvolumenstrom öffnen/schließen	L/min.	300 - 400	350 - 450	400 - 500	450 - 600	500 - 800	600 - 900	700 - 1000	900 - 1200
 Arbeitsdruck beim rotieren	Bar	180	180	180	180	180	180	180	180
 Ölvolumenstrom beim rotieren	L/min.	10	10	30	30	50	50	50	50
 Öffnen/schließen	Sec.	3.4 / 4.0	3.2 / 4.0	3.0 / 4.1	3.8 / 4.7	4.2 / 5.1	4.3 / 5.2	4.6 / 5.3	4.8 / 5.8

