



## DSP Couplings Brass

Half-coupling ringed shank D.S.P/A.R

DN D.S.P	ø/Shank	Art. Code	Material
40	45	DSP40SS45BR	Brass
65	70	DSP65SS70BR	Brass
100	110	DSP100SS110BR	Brass



Simple half-coupling Male B.S.P threaded without locking ring

DN D.S.P	ø/male	Art. Code	Material
40	1"1/2	DSP40M150BR	Brass
65	2"1/2	DSP65M250BR	Brass



Simple half-coupling Female B.S.P threaded without locking ring

DN D.S.P	ø/female	Art. Code	Material
40	1"1/2	DSPF150BR	Brass
65	2"1/2	DSPF250BR	Brass



Half-coupling with locking ring Male B.S.P threaded

DN D.S.P	ø/male	Art. Code	Material
40	1"1/2	DSP40ML150BR	Brass
65	2"1/2	DSP65ML250BR	Brass
100	4"	DSP100ML100BR	Brass



Half-coupling with locking ring Female B.S.P threaded

DN D.S.P	ø/female	Art. Code	Material
40	1"1/2	DSP40FL150BR	Brass
65	2"1/2	DSP65FL250BR	Brass
100	4"	DSP100FL400BR	Brass



Dust cap with locking ring and chain

DN D.S.P	Art. Code	Material
40	DSP40PLBR	Brass
65	DSP65PLBR	Brass
100	DSP100PLBR	Brass



Reduction coupling D.S.P and A.R with locking ring

DN D.S.P 1	DN 2	Art. Code	Material
40	Sym 20	DSPR40G20BR	Brass
65	D.S.P 40	DSPR6540BR	Brass
100	D.S.P 65	DSPR10065BR	Brass

