

# Ecofan®

## AIRDECO I & II

### CONTEMPORARY SERIES

- Next generation of Ecofans!
- Vesta-award winning, patent-pending design
- Superior performance
- Lower start temperature
- 4-year warranty



**AirDeco I**  
Model 8203

**AirDeco II**  
Model 8204

<b>AIRFLOW</b> CFM (at Max Achieved RPM per AMCA 230)	<b>160</b>	<b>190</b>
Max. Stove Temperature (°C)	<b>350</b>	<b>350</b>
Stove Temperature (°C) @ 50-CFM Airflow (per AMCA 230 Standard)	<b>65.5</b>	<b>70</b>
Blade Diameter (mm)	<b>200</b>	<b>230</b>
CE Compliant Blade (Round Edge)	✓	✓
CE Compliant Blade Speed	✓	✓

# Ecofan®

## ULTRAIR, AIRMAX, & BELAIR

### CLASSIC SERIES

- Patented design
- Warms your room up to **38% faster**
- Proven to reduce fuel usage by up to **18%**
- Designed for specific applications based on stove temperature and room size



**UltraAir**  
Model 810

**AirMax**  
Model 812

**BelAir**  
Model 806

<b>AIRFLOW</b> CFM (at Max Achieved RPM per AMCA 230)	<b>125</b>	<b>175</b>	<b>140</b>
Max. Stove Temperature (°C)	<b>350</b>	<b>350</b>	<b>200</b>
Stove Temperature (°C) @ 50-CFM Airflow (per AMCA 230 Standard)	<b>102</b>	<b>85</b>	<b>75</b>
Blade Diameter (mm)	<b>200</b>	<b>230</b>	<b>230</b>
CE Compliant Blade (Round Edge)	✓	✓	✓
CE Compliant Blade Speed	✓	✓	✓

# Ecofan®

## ORIGINAL & ORIGINAL MINI

### ORIGINAL SERIES

- The very first Ecofan!
- Original model has been in production for over **25 years**
- Two versions available:  
**8" Original** and **6.5" Original Mini**



**Original**  
Model 800

**Original Mini**  
Model 815

<b>AIRFLOW</b> CFM (at Max Achieved RPM per AMCA 230)	<b>100</b>	<b>85</b>
Max. Stove Temperature (°C)	<b>350</b>	<b>325</b>
Stove Temperature (°C) @ 50-CFM Airflow (per AMCA 230 Standard)	<b>111</b>	<b>83</b>
Blade Diameter (mm)	<b>206</b>	<b>160</b>
CE Compliant Blade (Round Edge)	✓	✓
CE Compliant Blade Speed	✓	✓



<b>HOW OUR COMPETITION STACKS UP</b>																			
<b>AIRFLOW</b> CFM (at Max Achieved RPM per AMCA 230)	99-20	116	113	87	80	115	82	96	85.25	92	102	16	63	79	65	125	97	112	120
Max. Stove Temperature (°C)	350	350	350	350	300	340	320	320	340	345	345								345
Stove Temperature (°C) @ 50-CFM Airflow (per AMCA 230 Standard)	173	135	111	160	134	110	194	194	172	155	115	N/A	122	105	136	158			125
Blade Diameter (mm)	210	165	206	204	204	180	150	180	180	185	205	108	153.4	227.97	167.76	208.73	193	208	150
CE Compliant Blade (Round Edge)	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗			✗
CE Compliant Blade Speed	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✓	✓	✓	✓			✓