

Installation scenarios Ultrasonic armatures

For industrial applications and R&D

Type 5 – single port armatures


Date: September 2023



5 - single port armatures

Application examples	Probe examples	Connection fittings
 Particle manipulation: ATR-FTIR Spectroscopy Raman Spectroscopy In-line Microscopy Cleaning: ATR-FTIR Spectroscopy Raman Spectroscopy Inline Microscopy FBRM 	 BlazeMetrics probes E&H Raman probes Tornado Hudson Marqmetrix Ballprobes Mettler Toledo ATR probes var. Hellma probes 	 Ingold DN25/DN40 GEA Varivent Type N or F Triclamp <u>Outer diameter DN19</u> Comopatible probe diameters: 6mm (1/4") 9,5mm (3/8") 12mm und 12,7mm (1/2") 14mm for outer diameter DN25 Additional compatible


The length L1 can be chosen before ordering. With the DN25 variant, only the diameter of the ultrasonic fitting changes.





probe diameter:19mm (3/4")

After consultation, special production request are always possible.





Disclaimer:

The information, text and illustrations in this document are for informational purposes only. We strive to provide accurate and up-to-date information, but the accuracy, completeness or timeliness of the content is not warranted. We reserve the rights to make changes to the content at any time.

Changes and Copyright:

All rights reserved. All trademarks and logos are the property of their respective owners.

Copying, reproducing or modifying any content of this document without express written permission is prohibited.

Further information:

Responsible for content and printing: usePAT GmbH, Austria

Copyright © 2023 usePAT GmbH, Vienna, Austria

usePAT GmbH

Schoenbrunner Strasse 231/2.01 1120 Vienna | Austria – Europe Phone: +43 660 83 45 674 E-mail: info@usePAT.com Web: www.usePAT.com